HET BREEDSTE GAMMA
MEET/MONITORINGSYSTEMEN

ABB SINGLE PHASE ELECTRICITY METER B21

EQ METERS IN STEEL VERSION

VWV metering is het platform waarop wij onze producten aanbieden. VWV metering biedt een ruim scala aan meters en toebehoren. Centraal hierbij staan het leveren en plaatsen van oplossingen waarbij draadloos en op afstand uitlezen en monitoren van meterstanden mogelijk wordt gemaakt. De oplossingen zijn uiterst flexibel en schaalbaar; en of het nu gaat om 20 dan wel 2000 verbruikers, VWV metering heeft een pasklare formule om in de gegeven omstandigheden tegemoet te komen aan de meest specifieke wensen van de klant. Wij kunnen daarom ook referenties voorleggen van verenigingen van eigenaren, syndicussen, woningbouwverenigingen tot en met energiebedrijven. **T.** +31 (0) 182 640 775 - **E.** service@vwvmetering.nl

SINGLE PHASE ELECTRICITY METER B21

The compact and versatile EQ meters B21 is a single phase meters with outstanding performance. It can be used in most of the common applications for reliable and trustworthy metering of energy usage. EQ meters B21 in Steel version can be used in standalone applications or metering network installations with the option of inbuilt M-Bus or Modbus.

GENERAL FEATURES

B21 is a single phase direct connected meter up to 65 A. The B21 is measuring active energy with accuracy class B (Cl. 1). The low rated or base currents of the meter ensures high dynamic performance with superior accuracy even at low currents. Navigation the meter is easily done via the push-buttons below the display. The exceptional low power consumption of the meter, less than 0.9 VA, makes it economical in the long run - an important feature specially for large meter populations.

COMMUNICATION

Data from B21 can be collected via pulse output or serial communication. The meter are equipped with a transistor output for 5-40 VDC external supply. It can be used for pulses proportionally to the measured energy or various alarms. The meter is also available with built-in serial communication interfaces for Modbus RTU (RS-485) or M-Bus.

INSTRUMENTATION

The B21 meter support reading of instrument values. A large number of electrical properties can be read. • Active power • Voltage • Current • Power factor • Frequency

APPROVALS

The B21 meter is type approved according to IEC as well as type approved and verified according to MID. MID is the Measure Instruments Directive 2004/22/EC from European Commission. The type approval is according to standards that covers all relevant technical aspects of the meter. These include climate conditions, electromagnetic compatibility (EMC), electrical requirements, mechanical requirements and accuracy.

ORDERING DETAILS

65 A direct connected, 2 DIN

Voltage V	Communication	Type	Order code	Weight 1 pc
Steel Active energy, pulse output, class B (Cl. 1)				
1 x 230 V AC	-	B21 111 - 100	2CMA100149R1000	0.14
	RS-485	B21 112 - 100	2CMA100150R1000	0.15
	M-Bus	B21 113 - 100	2CMA100151R1000	0.15

	B21
Voltage/current inputs	
Nominal voltage	230 V AC
Voltage range	220-240 VAC (-20% - +15%)
Power dissipation voltage circuits	0.9 VA (0,4 W) total
Power dissipation current circuits	0.014 VA (0.014 W) at 230 V AC and I_b
Base current I_b	5 A
Reference current I_{ref}	5 A
Transitional current I_tr	0.5 A
Maximum current I_{max}	65 A
Minimum current I_{min}	0.25 A
Starting current I_st	< 20 mA
Terminal wire area	1 - 25 mm^2
Recommended tightening torque	3 Nm
Communication	
Terminal wire area	0.5 - 1 mm^2
Recommended tightening torque	0.25 Nm
Pulse indicator (LED)	
Pulse frequency	1000 imp/kWh
Pulse length	40 ms
General data	
Frequency	50 or 60 Hz ± 5%
Accuracy Class	B (Cl. 1)
Active energy	1%
Display of energy	6 digit LCD
Environmental	
Operating temperature	-40°C - +70°C
Storage temperature	-40°C - +85°C
Humidity	75% yearly average, 95% on 30 days/year
Resistance to fire and heat	Terminal 960 °C, cover 650°C (IEC 60695-2-1)
Resistance to water and dust	IP20 on terminal block without protective enclosure and IP51 in protective enclosure, according to IEC 60529.
Mechanical environment	Class M1 in accordance with the Measuring Instrument Directive (MID). (2004/22/EC).
Electromagnetic environment	Class E2 in accordance with the Measuring Instrument Directive (MID), (2004/22/EC).
Outputs	
Current	2 - 100 mA
Voltage	5 - 40 VDC.
Pulse output frequency	Programmable: 1 - 999999 imp/kWh
Pulse length	Programmable: 10 - 990 ms
Terminal wire area	0.5 - 1 mm^2
Recommended tightening torque	0.25 Nm
EMC compatibility	
Impulse voltage test	6 kV 1.2/50µs (IEC 60060-1)
Surge voltage test	4 kV 1.2/50µs (IEC 61000-4-5)
Fast transient burst test	4kV (IEC 61000-4-4)
Immunity to electromagnetic HF-fields	80 MHz - 2 GHz (IEC 61000-4-6)
Immunity to conducted disturbance	150kHz - 80MHz (IEC 61000-4-6)
Immunity to disturbance with harmonics	2kHz - 150kHz
Radio frequency emission	EN 55022, class B (CISPR22)
Electrostatic discharge	15 kV (IEC 61000-4-2)
Standards	IEC 62052-11, IEC 62053-21 class 1, IEC 62054-21, GB/T 17215.211-2006, GB/T 17215.312-2008 class 1, GB 4208-2008, EN 50470-1, EN 50470-3 category B
Mechanical	
Material	Polycarbonate in transparent front glass. Glass reinforced polycarbonate in bottom case and upper case. Polycarbonate in terminal cover.
Dimensions	
Width	35 mm
Height	97 mm
Depth	65 mm
DIN modules	2

Wiring diagram B21



ABB AB
Meters
Box 1005
SE-611 29 NYKÖPING, Sweden
Telephone +46 155 29 50 00
Telefax +46 155 28 81 10

www.abb.com

© Copyright 2014 ABB. All rights reserved. Specification subject to change without notice.

This QR-code is linked to our web site www.abb.com/lowvoltage.
You will have to download a QR-code reader app to your phone in order to use it.

HET BREEDSTE GAMMA
MEET/MONITORINGSYSTEMEN

VOLLEDIG GRIP OP UW EIGEN METERPARK MET ONERGY

VOOR HET ACTUELE UITLEZEN VAN ALLE METERSTANDEN OP AFSTAND

De ervaring is dat woningbouwverenigingen, exploitanten, VvE's, vastgoedbeheerders, de volledige grip willen houden op hun meterpark. Er is meer en meer behoefte om dagelijks, wekelijks, maandelijks, niet alleen inzage te krijgen in de verbruiken maar bv. ook automatische meldingen te krijgen van eventuele storingen enz. Dit alles zonder afhankelijk te zijn van het betreffende meetbedrijf die de meetapparatuur geleverd heeft. Het ONERGY-platform kan dan ook alle meters inlezen en automatisch rapporteren onafhankelijk van het meterfabricaat.

HET ONERGY PLATFORM
ZOVEEL MEER DAN HET METEN
VAN VERBRUIK ALLEEN.

VWV metering
Hoge Ham 89 A - 5104 JC Dongen
T. +31 (0) 182 640 775
E. service@vwvgroup.nl

VWV België
Fr. Rooseveltlaan 349 - 9000 Gent
T. +32 (0) 9 265 02 72
E. service@vwvgroup.be

VWV GROUP
VWV kostenverdeling
VWV de energieboekhouders
VWV metering